

## RENTAL SPECIFICATION DB33S-400-11

### *Regenerating desiccant dryer*

- External-heat regeneration system
- No loss of compressed air for regeneration or cooling
- Pressure drop lower than 0.1 bar at full capacity
- Sophisticated PLC control and communication unit
- Parallel drying phase for steady dewpoint performance



Rental reference	DB33S-400-11
Make	DELAIR
Base model	DB33-S
Capacity	181 m <sup>3</sup> /min ( 10885 Nm <sup>3</sup> /h – 6400 cfm)
Working pressure	4 - 16 Bar(g) – (60 - 224 PSI (G))
Min/Max. inlet temp.	+5° to +40° C
Pressure dew point	-20 ° to -40° C
Air connections	DN200-PN16 (3x DN100-PN16 IN / 3x DN100-PN16 OUT)
Voltage	400 V, 50 H
Fan power	11 kW
Heating power	129 kW
Gross weight	11450 kg
Dimensions	5.1 x 2.5 x 3.4 m
Sound pressure	72 dB(A) (EN ISO 2151:2004), during blow-off 85 dB(A)

Machine is equipped with Pre and after filter.

Optional equipment:

- \*Air receiver tanks
- \*Alternative power supply
- \*Hoses and cables

\*\*\* LAST PAGE \*\*\*