

**RENTAL SPECIFICATION JO27-400-27**

***Regenerating desiccant dryer***

- External-heat regeneration system
- No loss of compressed air for regeneration or cooling
- Pressure drop lower than 0.1 bar at full capacity
- Sophisticated PLC control and communication unit
- Parallel drying phase for steady dewpoint performance



Rental reference	JO27-400-27
Make	JO (DELAIR)
Base model	DB27
Capacity*	58 m <sup>3</sup> /min ( 3480 m <sup>3</sup> /h – 2047 cfm)
Working pressure	4 - 10 Bar(g) – (56 - 140 PSI (G))
Discharge connection	DN100-PN16
Voltage	400 V, 3 Ph, 50 Hz
Absorbed power	56 kW (@ 50 Hz)
Gross weight	4.500 kg
Dimensions	3.1 x 2.25 x 3.1 m
Sound pressure	72 dB(A) (EN ISO 2151:2004), during blow-off 85 dB(A)

Machine is equipped with Pre and after (dust) filter.

\*Conditions: Working Pressure 7 Bar(g), 35°C inlet temp., ambient temp 25°C

For other operating conditions or special conditions please contact RTC Group BV

Optional equipment:

- \*Pressure reduction
- \*Air receiver tanks
- \*Alternative power supply
- \*Hoses and cables
- \*Air Compressors
- \*Booster compressor

\*\*\* LAST PAGE \*\*\*